

DGS-786HT

Digital TV Receiver Home STB



Main Feature:

- * DVB-Terrestrial Receiver for home Application
- * Able to Receive FTA/CA DVB Programmes
- * Compliance to DVB-T ETSI EN300744
- * Easy Installation and Programmes Selection
- * Full Features Remote Control with OSD
- * Includes EPG, Sub-title and Teletext
- * Support multilingual OSD selection
- * Support multi-sound channel broadcasting

Operating power	AC 100~240		
Power consumption	Max 8.5W		
Cross Weight	Approx. 0.8Kg		
Dimension	300mm(W) x 40mm(H) x 200mm (D)		
Tuner	DVB-T Receiver, Frequency Range: VHF III and UHF IV & V		
COFDM Modes	COFDM 2K and 8K carrier modes and all COFDM modulation types (QPSK, 16QAM and 64QAM)		
MPEG Transport	MPEG2 ISO/IEC 13818-1 Transport Stream at rate up to 100 Mbps.		
EPG	Electronic Program Guide Available		
Information	Present / Following Information Available		
Sub-Title	Sub-Title Available		
Teletext	Teletext VBI / OSD Available		
Video	MP@ML MPEG-2 decoding 720x576 pixels @ 25fps for PAL 720x480 pixels @ 30fps for NTSC		
Audio	Decompression MPEG-1/ 2 Layer I/II Samples Rates: 32kHz / 44.1kHz / 48kHz Sound Mode: Auto / Stereo / Mono / Right-Both / Left-Both		
Accessories	RC-UE609 Infra Red Remote Control External Infra Red Sensor Cable (5m) with Hardware Reset Button		
Software Upgraded	Through RJ-45 Port with RS-232 Adapter Cable		

Input

	Connector	Sensitivity	Impedance
RF Signal	IEC169-2 M	22dBu ~ 89dBu	75 ohm
AC Power Supply		Operation Range: 90~250V Max. Power Consumption: 8.5W	

Output

	Connector	Maximum Output	Impedance
Loop Through	IEC169-2 F		75 ohm
RF Out	IEC169-2 F	70dBu	75 ohm
Audio x2	RCA Jacks	1V @ 20k ohm	Over 10k ohm
			75 ohm, unbalanced, sync.negative, white peak
Video x1	RCA Jacks	1V p-p	
S-Video	mini-Circular	Y: 1V p-p; C:0.3V p-p	75 ohm